

| Model Number | Door Thickness Suffix |       | Maximum Door Travel in Feet | Maximum Door Panel Width in Feet | Maximum Door Weight |
|--------------|-----------------------|-------|-----------------------------|----------------------------------|---------------------|
|              | 2"-3"                 | 3"-4" |                             |                                  |                     |
| T40          | A                     | B     | 2.5                         | 2                                | 500 lbs             |
| T80          | A                     | B     | 4.5                         | 4                                | 500 lbs             |
| T80-2        | A                     | B     | 2.5 Bi-parting              | 2                                | 500 lbs per panel   |
| T120         | A                     | B     | 6.5                         | 6                                | 500 lbs             |
| T120-2       | A                     | B     | 3.5 Bi-parting              | 3                                | 500 lbs per panel   |
| T160         | A                     | B     | 8.5                         | 8                                | 500 lbs             |
| T160-2       | A                     | B     | 4.5 Bi-parting              | 4                                | 500 lbs per panel   |

The Zephyr Track System can be used in conjunction with Air-Lec sliding door operators or as a stand-alone track system for a manual door.

The Zephyr Track System Design reduces freight costs and speeds delivery.

#### TYPICAL REQUIREMENTS FOR MANUAL OPERATION

##### Single Doors Under 500 lbs:

- 1 T120A Zephyr Track System
- 1 14812 End Guide & Stop
- 1 14814 Binder Stop
- 1 14816 Stay Roller

##### Bi-Parting Doors Under 500 lbs Each:

- 1 T120-2A Zephyr Bi-Part Track System
- 2 14812 End Guides & Stops
- 2 14816 Stay Rollers

#### TYPICAL REQUIREMENTS FOR AIR-LEC AUTOMATIC OPERATION

##### Single Doors Under 500 lbs:

- 1 T120A Zephyr Track System
- 1 0260 Overcenter Door Operator
- 1 E300 or A30 Pull-Cord Control Kit
- 1 6148 Filter-Regulator
- 1 5487 Regulator Mounting Bracket
- 1 6151-1 Dehydrator (for moist air)
- 1 14812 End Guide & Stop
- 1 14814 Binder Stop
- 1 14816 Stay Roller

##### Bi-Parting Doors Under 500 lbs Each:

- 1 T120-2A Zephyr Bi-Part Track System
- 2 0260 Overcenter Door Operator
- 1 E400 or A40 Pull-Cord Control Kit
- 1 6148 Filter-Regulator
- 1 5487 Regulator Mounting Bracket
- 1 6151-1 Dehydrator (for moist air)
- 2 14812 End Guides & Stops
- 2 14816 Stay Rollers



## AIR-LEC INDUSTRIES, INC.

3300 Commercial Ave., Madison, Wisconsin 53714-1499

Phone: (608) 244-4754 Fax: (608) 246-7676 Website: [www.air-lec.com](http://www.air-lec.com)